

# EQRA24L1H-33.8688M

[Click part number to visit Part Number Details page](#)

## REGULATORY COMPLIANCE (Data Sheet downloaded on May 27, 2020)


[Click badges to download compliance docs](#)

Regulatory Compliance standards are subject to updates by governing bodies. Click the badges to download the latest compliance docs for this part number directly from Ecliptek.



## ITEM DESCRIPTION

Quartz Crystal Clock Oscillators XO (SPXO) LVCMOS (CMOS) 2.8Vdc 6 Pad 3.2mm x 5.0mm Ceramic Surface Mount (SMD) 33.8688MHz  $\pm 25$ ppm over -40°C to +85°C

## ELECTRICAL SPECIFICATIONS

|   |   |
|---|---|
| Nominal Frequency                             | 33.8688MHz  |
| Frequency Tolerance/Stability                 | $\pm 25$ ppm Maximum over -40°C to +85°C (Inclusive of all conditions: Calibration Tolerance (at 25°C), Frequency Stability over the Operating Temperature Range, Supply Voltage Change and Output Load Change)                                     |
| Aging at 25°C                                 | $\pm 2$ ppm Maximum First Year, $\pm 10$ ppm/10 Years Maximum   |
| Supply Voltage                                | 2.8Vdc $\pm 5\%$  |
| Input Current                                 | 20mA Maximum (Unloaded)   |
| Output Voltage Logic High (Voh)               | 90% of Vdd Minimum (IOH = -4mA)   |
| Output Voltage Logic Low (Vol)                | 10% of Vdd Maximum (IOL = +4mA)   |
| Rise/Fall Time                                | 3nSec Maximum (Measured at 10% to 90% of Waveform)  |
| Duty Cycle                                    | 50 $\pm 10$ (%) (Measured at 50% of Waveform)   |
| Load Drive Capability                         | 15pF Maximum  |
| Output Logic Type                             | CMOS  |
| Phase Noise                                   | -64dBc/Hz at 10Hz offset; -96dBc/Hz at 100Hz offset; -124dBc/Hz at 1kHz offset; -131dBc/Hz at 10kHz offset; -132dBc/Hz at 100kHz offset; -149dBc/Hz at 1MHz offset; -157dBc/Hz at 10MHz offset; -159dBc/Hz at 20MHz offset (All Values are Typical) |
| Output Control Function                       | Output Enable (OE)  |
| Output Control Input Voltage Logic High (Vih) | 90% of Vdd Minimum or No Connect to Enable Output   |
| Output Control Input Voltage Logic Low (Vil)  | 10% of Vdd Maximum to Disable Output (High Impedance)   |
| Output Enable Time                            | 100nSec Maximum   |
| Output Disable Time                           | 50nSec Maximum  |
| Output Enable Current                         | 15mA Maximum (Without Load (Pin 1 = Ground))  |
| RMS Phase Jitter                              | 1.5pSec Maximum (Fj=12kHz to 20MHz (Random))  |
| Period Jitter (Deterministic)                 | 0.2pSec Typical   |
| Period Jitter (Random)                        | 2pSec Typical   |
| Period Jitter (RMS)                           | 3pSec Maximum   |
| Period Jitter (pk-pk)                         | 30pSec Maximum  |
| Start Up Time                                 | 10mSec Maximum  |
| Storage Temperature Range                     | -55°C to +125°C   |

## ENVIRONMENTAL & MECHANICAL SPECIFICATIONS

|                              |   |
|------------------------------|---|
| ESD Susceptibility           | MIL-STD-883, Method 3015, Class 1, HBM: 1500V |
| Fine Leak Test               | MIL-STD-883, Method 1014, Condition A         |
| Flammability                 | UL94-V0                                       |
| Gross Leak Test              | MIL-STD-883, Method 1014, Condition C         |
| Mechanical Shock             | MIL-STD-883, Method 2002, Condition B         |
| Moisture Resistance          | MIL-STD-883, Method 1004                      |
| Moisture Sensitivity         | J-STD-020, MSL 1                              |
| Resistance to Soldering Heat | MIL-STD-202, Method 210, Condition K          |

**EQRA24L1H-33.8688M** [Click part number to visit Part Number Details page](#)**ENVIRONMENTAL & MECHANICAL SPECIFICATIONS CONTINUED**

|                               |                                       |
|-------------------------------|---------------------------------------|
| <b>Resistance to Solvents</b> | MIL-STD-202, Method 215               |
| <b>Solderability</b>          | MIL-STD-883, Method 2003              |
| <b>Temperature Cycling</b>    | MIL-STD-883, Method 1010, Condition B |
| <b>Vibration</b>              | MIL-STD-883, Method 2007, Condition A |

## EQRA24L1H-33.8688M [Click part number to visit Part Number Details page](#)

### MECHANICAL DIMENSIONS (all dimensions in millimeters)



| PIN | CONNECTION         |
|-----|--------------------|
| 1   | Output Enable (OE) |
| 2   | Do Not Connect     |
| 3   | Case/Ground        |
| 4   | Output             |
| 5   | Do Not Connect     |
| 6   | Supply Voltage     |

| LINE | MARKING  |
|------|--|
| 1    | <b>E33.868</b><br><i>E=Ecliptek Designator</i>                 |
| 2    | <b>XXXXX</b><br><i>XXXXX=Ecliptek Manufacturing Identifier</i> |

### Suggested Solder Pad Layout

All Dimensions in Millimeters



All Tolerances are  $\pm 0.1$

**EQRA24L1H-33.8688M** [Click part number to visit Part Number Details page](#)

**OUTPUT WAVEFORM & TIMING DIAGRAM**



# EQRA24L1H-33.8688M

[Click part number to visit Part Number Details page](#)

## Test Circuit for CMOS Output



Note 1: An external 0.01µF ceramic bypass capacitor in parallel with a 0.1µF high frequency ceramic bypass capacitor close (less than 2mm) to the package ground and supply voltage pin is required.

Note 2: A low capacitance (<12pF), 10X attenuation factor, high impedance (>10Mohms), and high bandwidth (>300MHz) passive probe is recommended.

Note 3: Capacitance value C<sub>L</sub> includes sum of all probe and fixture capacitance.

# EQRA24L1H-33.8688M

[Click part number to visit Part Number Details page](#)

## Recommended Solder Reflow Methods



### High Temperature Infrared/Convection

|  |   |
|--|---|
| <b>Ts MAX to Tl (Ramp-up Rate)</b>         | 3°C/Second Maximum                                |
| <b>Preheat</b>                             |   |
| - Temperature Minimum (Ts MIN)             | 150°C   |
| - Temperature Typical (Ts TYP)             | 175°C   |
| - Temperature Maximum (Ts MAX)             | 200°C   |
| - Time (ts MIN)                            | 60 - 180 Seconds                                  |
| <b>Ramp-up Rate (Tl to Tp)</b>             | 3°C/Second Maximum                                |
| <b>Time Maintained Above:</b>              |   |
| - Temperature (Tl)                         | 217°C   |
| - Time (tL)                                | 60 - 150 Seconds                                  |
| <b>Peak Temperature (Tp)</b>               | 260°C Maximum for 10 Seconds Maximum              |
| <b>Target Peak Temperature (Tp Target)</b> | 250°C +0/-5°C                                     |
| <b>Time within 5°C of actual peak (tp)</b> | 20 - 40 Seconds                                   |
| <b>Ramp-down Rate</b>                      | 6°C/Second Maximum                                |
| <b>Time 25°C to Peak Temperature (t)</b>   | 8 Minutes Maximum                                 |
| <b>Moisture Sensitivity Level</b>          | Level 1   |
| <b>Additional Notes</b>                    | Temperatures shown are applied to body of device. |

# EQRA24L1H-33.8688M

[Click part number to visit Part Number Details page](#)

## Recommended Solder Reflow Methods



### Low Temperature Infrared/Convection 240°C

|  |  |
|--|--|
| <b>T<sub>s</sub> MAX to T<sub>L</sub> (Ramp-up Rate)</b> | 5°C/Second Maximum                                     |
| <b>Preheat</b>   |  |
| - Temperature Minimum (T <sub>s</sub> MIN)               | N/A  |
| - Temperature Typical (T <sub>s</sub> TYP)               | 150°C  |
| - Temperature Maximum (T <sub>s</sub> MAX)               | N/A  |
| - Time (t <sub>s</sub> MIN)                              | 60 - 120 Seconds                                       |
| <b>Ramp-up Rate (T<sub>L</sub> to T<sub>P</sub>)</b>     | 5°C/Second Maximum                                     |
| <b>Time Maintained Above:</b>                            |  |
| - Temperature (T <sub>L</sub> )                          | 150°C  |
| - Time (t <sub>L</sub> )                                 | 200 Seconds Maximum                                    |
| <b>Peak Temperature (T<sub>P</sub>)</b>                  | 240°C Maximum  |
| <b>Target Peak Temperature (T<sub>P</sub> Target)</b>    | 240°C Maximum 2 Times / 230°C Maximum 1 Time           |
| <b>Time within 5°C of actual peak (t<sub>p</sub>)</b>    | 10 Seconds Maximum 2 Times / 80 Seconds Maximum 1 Time |
| <b>Ramp-down Rate</b>                                    | 5°C/Second Maximum                                     |
| <b>Time 25°C to Peak Temperature (t)</b>                 | N/A  |
| <b>Moisture Sensitivity Level</b>                        | Level 1  |
| <b>Additional Notes</b>                                  | Temperatures shown are applied to body of device.      |

### Low Temperature Manual Soldering

185°C Maximum for 10 Seconds Maximum, 2 times Maximum. (Temperatures shown are applied to body of device.)

### High Temperature Manual Soldering

260°C Maximum for 5 Seconds Maximum, 2 times Maximum. (Temperatures shown are applied to body of device.)